

# Oakton Community College District 535

Procurement Department, Room 1240  
1600 E. Golf Rd., Des Plaines, IL 60016  
847-635-1635

**Invitation to Bid # 1221-22-02**  
**Issue Date: December 21, 2022**

**Mandatory Pre-Bid Date: Wednesday, January 11, 2023 at 11:00 am**

**Bids will be received in the Procurement Office at the above address until  
11:00 am on Wednesday, January 25, 2023**  
Bids will be publicly opened at this time. Late bids will not be accepted.

---

## Courtyard Rehabilitation

The College is accepting bids for courtyard rehabilitation at the Des Plaines Campus.

**This bid consists of 2 documents:**

- 1) Business Specifications (this document)
- 2) Oakton Community College Courtyard Rehabilitation Plans
  - a. Manhard Consulting Civil Plans dated 11/04/22
  - b. ECT Landscaping Plans dated 11/04/22
  - c. Kluber Electrical Plans dated 11/04/22

**A mandatory pre-bid meeting will be held on Wednesday, January 11, 2023 starting at 11:00 am at the College's Des Plaines campus, 1600 E. Golf Road, Suite 1240.**

**Only contractors who attend the pre-bid meeting will be allowed to submit a bid.**

Any questions regarding this bid must be submitted in writing via email by 11:00 am on January 18, 2023  
Questions will be answered through an addendum and must be submitted to the following individuals:

Joe Scifo, Director of Facilities, [jscifo@oakton.edu](mailto:jscifo@oakton.edu)  
Rich Schwass, Construction Manager at [rschwass@oakton.edu](mailto:rschwass@oakton.edu)  
Jim Frayn, Manhard Consulting at [jfrayn@manhard.com](mailto:jfrayn@manhard.com)  
Trinh Than, Purchasing Manager at [tthan@oakton.edu](mailto:tthan@oakton.edu)

---

Oakton Community College District 535 is exempt from all Federal, State, and Municipal Taxes.

I have examined the specifications and instructions included herein and agree, provided I am awarded a contract within 60 days of the bid due date, to provide the specified items for the sum shown in accordance with the terms stated herein. All deviations from the specifications and terms are in writing and attached hereto. I offer the following discount terms

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_

Address: \_\_\_\_\_ City/St/Zip: \_\_\_\_\_

Name: \_\_\_\_\_ Title: \_\_\_\_\_

Phone #: \_\_\_\_\_ Fax #: \_\_\_\_\_

Signature: \_\_\_\_\_ E-mail: \_\_\_\_\_

1. The Unit Price Bid Items Descriptions table on pages 27 and 28 will be deleted entirely and be replaced with the following:

**UNIT PRICE BID ITEMS DESCRIPTIONS  
 COURTYARD REHABILITATION**

The work includes providing all necessary labor, material and equipment to complete all the site improvements as detailed in the contract documents for the Des Plaines Campus of Oakton Community College, including, but not limited to full depth asphalt removal and replacement, mill and overlay, crack sealing, etc.

BID - SCHEDULE OF PRICES						Date Prepared: 2022/10/27
Construction Pay Items						
ITEM	DESCRIPTION	QUANTITY	UNIT	Unit Price <sup>1</sup>	UNIT PRICE	Extension
<b>SCHEDULE I - LANDSCAPING IMPROVEMENTS</b>						
<b>SUBTOTAL A - PLANT REMOVALS AND PROTECTION (L1.0)</b>						
1	PLANT/SOIL PROTECTION FENCE	505	LF			
2	TREE PRUNING FOR TREES TO REMAIN		LS			
3	REMOVE TREE AND GRIND STUMP	22	EA			
4	REMOVE/GRIND STUMP	6	EA			
5	REMOVE AND DISPOSE OF STEEL EDGING		LS			
6	REMOVE AND DISPOSE OF MISCELLANEOUS BRICK/CONCRETE BLOCK/ROCKS/POTTING SOIL		LS			
7	RELOCATE BUXUS X 'GREEN MOUNTAIN'	12	EA			
8	TOPSOIL IMPORT AND PLACEMENT	96	CY			
9	SUBGRADE PREPARATION FOR NEW PLANTING AREAS	2338	SF			
10	AMEND EXISTING TOPSOIL W/ COMPOST	82	CY			
11	CLEAR AND GRUB WOODY VEGETATION	29	SY			
12	RELOCATE STATUE		LS			
13	POWER WASH EXISTING CONCRETE SEATWALLS		LS			
14	HERBACEOUS PLANT REMOVAL (HERBICIDING)		LS			
<b>TOTAL SUBTOTAL A - PLANT REMOVALS AND PROTECTION (L1.0)</b>						
<b>SUBTOTAL B - PLANTING PLAN (L2.0)</b>						
15	MULCH - DBL. SHREDDED HARDWOOD BARK MULCH	231	CY			
16	MULCH - PARTIALLY DECOMPOSED LEAF MULCH	36	CY			
17	TURFGRASS SOD	49	SY			
18	COBBLE PAVING	27	SF			
19	2 YEAR PLANT WARRANTY/MAINTENANCE FOR HERBACEOUS PERENNEALS/GRASSES	1	LS			
20	1 YEAR PLANT WARRANTY/MAINTENANCE FOR WOODY TREES/SHRUBS	1	LS			
21	1 YEAR PLANT WARRANTY/MAINTENANCE FOR TURFGRASS	1	LS			
22	BENCH AND FOOTINGS	5	EA			
<b>TOTAL SUBTOTAL B - PLANTING PLAN (L2.0)</b>						
<b>SUBTOTAL C - PLANTING PLAN (L2.1)</b>						
<b>SMALL TREES</b>						
23	AMELANCHIER LAEVIS, ALLEGHENY SERVICEBERRY (B&B, 8' HT)	4	EA			
24	CARPINUS CAROLINIANA, BLUE BEECH (B&B, 8' HT)	2	EA			
25	HAMAMELIS VIRGINIANA, WITCH HAZEL (B&B, 8' HT)	4	EA			
<b>SHRUBS</b>						
26	AESCLUSUS PARVIFLORA, BOTTLEBRUSH BUCKEYE (CONT, 5 GAL)	9	EA			
27	HYDRANGEA PANICULATA 'LITTLE LIME', LITTLE LIME HYDRANGEA (CONT, 3 GAL)	8	EA			
28	ITEA VIRGINICA 'HENRY'S GARNET', HENRY'S GARNET VIRGINIA SWEETSPIRE (CONT, 4 GAL)	31	EA			
29	KERRIA JAPONICA, JAPANESE ROSE (CONT, 5 GAL)	5	EA			
30	LINDERA BENZOIN, SPICEBUSH (B&B, 5' HT)	1	EA			
31	RIBES ALPINUM 'GREEN MOUND', GREEN MOUND MOUNTAIN CURRANT (CONT, 3 GAL)	38	EA			
32	SEPHENANDRA INCISA 'CRISPA', LACE SHRUB (CONT, 3 GAL)	31	EA			
33	VIBURNUM ACERIFOLIUM, MAPLELEAF VIBURNUM (B&B, 4' HT)	19	EA			
<b>PERENNIALS</b>						
34	ARALIA CORDATA 'SUN KING', GOLDEN JAPANESE SPIKENARD (CONT, 1 GAL)	10	EA			
35	ASARAM CANADENSE, WILD GINGER (CONT, 1 PT)	1549	EA			
36	ASTER DIVARICATUS, WHITE WOOD ASTER (CONT, 1 PT)	61	EA			
37	CAREX ELATA 'AUREA', BOWLES GOLDEN SEDGE (CONT, 1 QT)	73	EA			
38	CAREX LAXICULMIS 'HOBB' BUNNY BLUE, BUNNY BLUE CLAUSCOUS WOODLAND SEDGE	263	EA			
39	CAREX SPRENGELII, LONG BEAKED SEDGE (CONT, 1QT)	99	EA			
40	CAREX PENNSYLVANICA, PENN SEDGE (CONT, 1 QT)	30	EA			
41	CAULOPHYLLUM THALICTROIDES, BLUE COHOSH (CONT, 1 GAL)	12	EA			
42	CHELONE GLABRA, TURTLEHEAD (CONT, 1 GAL)	94	EA			
43	CROCUS CHRYSANTHUS 'CREAM BEAUTY', CREAM BEAUTY CROCUS (BULB, TOP SIZE)	549	EA			
44	DESCHAMPsia CESPITOSA 'GOLDTAU', GOLDTAU TUFTED HAIR GRASS (CONT, 1 QT)	79	EA			
45	ECHINACEA PALLIDA, PALE PURPLE CONEFLOWER (CONT, 1 QT)	93	EA			
46	GERANIUM MACULATUM, WILD GERANIUM (CONT, 1 QT)	45	EA			
47	HEUCHERA VILLOSA, HAIRY ALLUMROOT (CONT, 1 PT)	72	EA			
48	HOSTA 'MAY', MAY HOSTA (CONT, 1 QT)	75	EA			
49	HOSTA 'ROYAL STANDARD', ROYAL STANDARD HOSTA (CONT, 1 GAL)	116	EA			
50	HOSTA TARDIANA 'JUNE', JUNE HOSTA (CONT, 1 QT)	48	EA			
51	LIGULARIA 'BRITT-MARIE CRAWFORD', LEOPARD PLANT (CONT, 1 GAL)	7	EA			
52	MONARDA FISTULOSA, BEE BALM (CONT, 1 GAL)	8	EA			
53	ONOCLEA SENSIBILIS, SENSITIVE FERN (CONT, 1 QT)	43	EA			
54	PHLOX DIVARICATA, WOODLAND PHLOX (CONT, 1 PT)	48	EA			
55	POLYGONATUM ODORATUM VAR. PLURIFLORUM 'VARIEGATUM', VARIEGATED SOLOMON'S SEAL (CONT, 1 QT)	482	EA			
56	RUDBECKIA FULGIDA V. FULGIDA, BLACK-EYED SUSAN (CONT, 1 QT)	34	EA			
57	RUELLIA HUMILIS, PRAIRIE PETUNIA (CONT, 1 QT)	61	EA			

ITEM	DESCRIPTION	QUANTITY	UNIT	Unit Price <sup>1</sup>	UNIT PRICE	Extension
58	SESLERIA AUTUMNALIS, AUTUMN MOOR GRASS (CONT, 2 QT)	141	EA			
59	SPOROBOLUS HETEROLEPIS, PRAIRIE DROPSEED (CONT, 1 QT)	218	EA			
60	STACHYS MONIERI 'HUMMELO', BETONY (CONT, 1 GAL)	20	EA			
	<b>FERNS</b>					
61	ASPLENIUM PLATYNEURON, EBONY SPLEENWORT (CONT, 1 PT)	13	EA			
62	MATTEUCCIA STRUTHIOPTERIS, OSTRITCH FERN (CONT, 1 PT)	19	EA			
63	ONOCLEA SENSIBILIS, SENSITIVE FERN (CONT, 1 QT)	43	EA			
64	OSMUNDASTRUM CINNAMOMEUM, CINNAMON FERN (CONT, 1 PT)	90	EA			
65	POLYSTICHUM ACROSTICHOIDES, CHRISTMAS FERN (CONT, 1 PT)	48	EA			
	<b>VINES</b>					
66	PARTHENOCISSUS QUINQUEFOLIA, VIRGINIA CREEPER (CONT, 1 QT)	43	EA			
	<b>TOTAL SUBTOTAL C- PLANTING PLAN (L2.1)</b>					
	<b>TOTAL SCHEDULE I -LANDSCAPING IMPROVEMENTS</b>					
	<b>SCHEDULE II - SITE IMPROVEMENTS (CIVIL SCOPE)</b>					
67	EXCESS SPOILS REMOVAL – PAVERS (INCLUDES REMOVAL OF OLD AGGREGATE AND OFFSITE DISPOSAL BY CONTRACTOR)		LS			
68	EXCESS SPOILS REMOVAL – PAVEMENT		LS			
69	AGGREGATE FILL IN OLD CIRCULAR SEATING AREA		CY			
70	SAWCUT PAVEMENT, FULL DEPTH		LF			
71	MOBILIZATION		LS			
72	CONCRETE STAIR REMOVAL		LS			
73	EX. STAIR RAIL REMOVAL		LS			
74	TEMPORARY SEEDING		SY			
75	SUBGRADE PREPARATION - FINE GRADING		SY			
76	AGGREGATE BASE COURSE - 4"		SY			
77	AGGREGATE BASE COURSE - 6", CA-6 GRADE 9		SY			
78	PCC PAVEMENT 8"		SY			
79	CONCRETE BARRIER CURB		LF			
80	PAVEMENT REMOVAL, FULL DEPTH		SY			
81	BRUSSELS BLOCK XL UNILOCK PAVERS		SF			
82	BRUSSELS BLOCK UNILOCK PAVERS INSTALLATION		SF			
83	SANITARY FRAME ADJUSTMENT		EA			
84	TRENCH DRAIN FRAME AND GRATE AND UNDERGROUND APPURTENANCE ADJUSTMENT		LS			
85	INLET ABANDONED IN PLACE		LS			
86	STORM DRAIN ABANDONED IN PLACE		LS			
87	TEMPORARY INLET PROTECTION		EA			
88	FULL DEPTH PAVEMENT PATCHING		LS			
89	CRACK SEALING		LS			
90	ADJUST ELECTRICAL JUNCTION BOX TO GRADE		EA			
91	DRILL WEEP HOLES INTO CONCRETE WALL		LS			
92	6" TRENCH DRAIN FRAME AND GRATE		EA			
93	2'-0" DIAMETER INLET		EA			
94	8" PVC STORM SEWER PIPE AND TRENCH BACKFILL		LF			
	<b>TOTAL SCHEDULE II -SITE IMPROVEMENTS (CIVIL SCOPE)</b>					
	<b>SCHEDULE III - ELECTRICAL IMPROVEMENTS</b>					
95	Pole Mount Luminaires Types F1A and F1B with Concrete Foundations		LS			
96	Pole Mount Luminaires Type F1A with Helical Pile Foundation		LS			
97	In-Grade Flood Luminaire Type F2		LS			
98	Electrical Demolition		LS			
99	Branch Circuitry and Pull Boxes		LS			
100	Electrical Balance of Work		LS			
101	Painted Steel Wall/Post-Mounted Handrail		LS			
	<b>TOTAL SCHEDULE III - ELECTRICAL IMPROVEMENTS</b>					
	PERFORMANCE AND PAYMENT BOND		LS			
	CCDD Spoil Removal	10	CY			
	<b>GRAND TOTAL</b>					

Use Quantities where shown above. Provide quantities where not shown. . All bid items are lump sum.

Company: \_\_\_\_\_

Signature: \_\_\_\_\_ Email: \_\_\_\_\_




- 
2. The Oakton Community College Courtyard Rehabilitation Plans will be deleted entirely and replaced with the following:

# OAKTON COMMUNITY COLLEGE COURTYARD REHABILITATION

1600 EAST GOLF ROAD  
DES PLAINES, ILLINOIS



## STANDARD SYMBOLS

### EXISTING



STORM SEWER  
SANITARY SEWER  
COMBINED SEWER  
FORCEMAIN  
DRAINTILE  
WATER MAIN  
ELECTRIC  
GAS  
TELEPHONE  
OVERHEAD WIRES  
SANITARY MANHOLE  
STORM MANHOLE  
CATCH BASIN  
STORM INLET  
CLEANOUT  
HAY BALES  
RIP RAP  
VALVE IN VAULT  
VALVE IN BOX  
FIRE HYDRANT  
BUFFALO BOX  
FLARED END SECTION  
STREET LIGHT  
SUMMIT / LOW POINT  
RIM ELEVATION  
INVERT ELEVATION  
DITCH OR SWALE  
DIRECTION OF FLOW  
OVERFLOW RELIEF SWALE  
1 FOOT CONTOURS  
CURB AND GUTTER  
DEPRESSED  
CURB AND GUTTER  
REVERSE CURB  
AND GUTTER  
SIDEWALK  
DETECTABLE WARNINGS  
PROPERTY LINE  
EASEMENT LINE  
SETBACK LINE  
MAIL BOX  
SIGN  
TRAFFIC SIGNAL  
POWER POLE  
GUY WIRE  
GAS VALVE  
HANDHOLE  
ELECTRICAL EQUIPMENT  
TELEPHONE EQUIPMENT  
CHAIN-LINK FENCE  
SPOT ELEVATION  
BRUSH/TREE LINE  
DECIDUOUS TREE WITH  
TRUNK DIA. IN INCHES (TBR)  
CONIFEROUS TREE WITH  
HEIGHT IN FEET (TBR)  
SILT FENCE  
RETAINING WALL  
WETLAND

### PROPOSED



LOCATION MAP  
N.T.S.

**OWNER/CLIENT:**  
OAKTON COMMUNITY COLLEGE  
1600 E. GOLF ROAD  
DES PLAINES, ILLINOIS  
(847) 635-1600  
CONTACT:  
RICHARD SCHWASS  
SENIOR MANAGER OF  
CAMPUS FACILITIES

INDEX OF SHEETS	
SHEET NO.	DESCRIPTION
1	TITLE SHEET
2	EXISTING CONDITIONS AND DEMOLITION PLAN
3	SITE DIMENSIONAL AND PAVING PLAN
4	GRADING PLAN
5	UTILITY PLAN
6	CONSTRUCTION DETAILS
7	CONSTRUCTION SPECIFICATIONS
L1.0	PLANT REMOVAL AND PROTECTION
L2.0	PLANTING PLAN
L2.1	PLANT SCHEDULE
L3.0	LANDSCAPE DETAILS
E1.0	ELECTRICAL SITE PLANS - UPPER COURTYARD
E2.0	ARCHITECTURAL AND ELECTRICAL PLANS - LOWER COURTYARD

### NOTES:

- THE BOUNDARY LINES AND TOPOGRAPHY FOR THIS PROJECT ARE BASED ON A FIELD SURVEY COMPLETED BY MANHARD CONSULTING, LTD. ON APRIL 14, 2022. THE CONTRACTOR SHALL VERIFY THE EXACT LOCATION OF THE EXISTING CONDITIONS PRIOR TO CONSTRUCTION AND SHALL IMMEDIATELY NOTIFY MANHARD CONSULTING AND THE CLIENT IN WRITING OF ANY DIFFERING CONDITIONS.
- CITY OF DES PLAINES NOTES AND PLAN DETAILS SUPERCEDE ALL OTHERS.
- CONTRACTOR TO FIELD VERIFY ALL HANDICAP ACCESSIBLE ROUTES ARE IN CONFORMANCE WITH ALL ADA AND IAC REQUIREMENTS AND GUIDELINES PRIOR TO COMMENCEMENT OF WORK ON SITE. CONTRACTOR TO NOTIFY ENGINEER OF ANY DISCREPANCIES.

### BENCHMARKS:

**REFERENCE BENCHMARK:**  
CITY OF DES PLAINES BENCHMARK #65: CHISELED SQUARE ON TOP OF HEADWALL ON THE SOUTH SIDE OF CENTRAL ROAD AND THE WEST SIDE OF DES PLAINES RIVER.

ELEVATION=639.60

DATUM=NAVD88

### SITE BENCHMARK 10:

CUT SQUARE ON THE WEST SIDE OF A CONCRETE LIGHT POLE BASE AT THE NORTHEAST ENTRANCE TO PRESIDENT'S COURTYARD IN THE MAIN BUILDING AT OAKTON COMMUNITY COLLEGE. APPROXIMATELY 17 FEET EAST OF THE NORTHWEST BUILDING CORNER OF THE ENTRANCE AND APPROXIMATELY 28 FEET NORTHWEST OF THE SOUTHEAST BUILDING CORNER OF THE ENTRANCE.

ELEVATION=637.38

DATUM=NAVD88

### SITE BENCHMARK 11:

NORTHWEST FLANGE BOLT ON A FIRE HYDRANT ON THE NORTH SIDE OF THE MAIN BUILDING AT OAKTON COMMUNITY COLLEGE. APPROXIMATELY 200 FEET EAST OF THE NORTHEAST ENTRANCE TO PRESIDENT'S COURTYARD AND APPROXIMATELY 15 FEET SOUTHWEST OF THE SOUTHWEST EDGE OF WATER OF OAKTON LAKE.

ELEVATION=634.24

DATUM=NAVD88

### SITE BENCHMARK 12:

SOUTH ARROW BOLT ON A FIRE HYDRANT NEAR THE NORTHEAST CORNER OF THE MAIN BUILDING AT OAKTON COMMUNITY COLLEGE, APPROXIMATELY 125 FEET SOUTHWEST OF THE SOUTHWEST CORNER OF THE MARGARET BURKE LEE SCIENCE AND HEALTH CAREERS CENTER BUILDING AND APPROXIMATELY 40 FEET SOUTHWEST OF THE SOUTHWEST EDGE OF WATER OF OAKTON LAKE.

ELEVATION=637.61

DATUM=NAVD88

## ABBREVIATIONS

ADJ AGG. ARCH B.A.M. B-B B/C B/P B/W B-BOX BIT. BM B.O. C.B. C. CMP CNTRL C.O. CONC. CY D DIA. DIP DIWM DS DT E E-E ELEV. E/P EX. F-E F-F F.F. FES	ADJUST AGGREGATE ARCHITECT BITUMINOUS AGGREGATE MIXTURE BACK TO BACK BACK OF CURB BOTTOM OF PIPE BACK OF WALK BUFFALO BOX BITUMINOUS BENCHMARK BY OTHERS COMMERCIAL ENTRANCE CATCH BASIN CENTERLINE CORRUGATED METAL PIPE CONTROL CLEANOUT CONCRETE CUBIC YARD DITCH DIAMETER DUCTILE IRON PIPE DUCTILE IRON WATER MAIN DOWNSPOUT DRAIN TILE ELECTRIC EDGE TO EDGE ELEVATION EDGE OF PAVEMENT EXISTING FIELD ENTRANCE FACE TO FACE FINISHED FLOOR FLARED END SECTION	F/L FM G G/F GW HDWL HH HWL HYD. INL. INV. IP L L.T. LX. MB M/E MH MIN. NWL P.E. P.C. PCC PGL P.I. P PP PROP. PT PVC P.V. P.V.T. P P.U.D.E. R	FLOW LINE FORCE MAIN GROUND GRADE AT FOUNDATION GUY WIRE HEADWALL HANDHOLE HIGH WATER LEVEL HYDRANT INLET INVERT IRON PIPE LEFT MAXIMUM MAILBOX MEET EXISTING MANHOLE MINIMUM NORMAL WATER LEVEL PRIVATE ENTRANCE POINT OF CURVATURE POINT OF COMPOUND CURVE PROFILE GRADE LINE POINT OF INTERSECTION PROPERTY LINE POWER POLE PROPOSED POINT OF TANGENCY POLYVINYL CHLORIDE PIPE POINT OF VERTICAL CURVATURE POINT OF VERTICAL INTERSECTION POINT OF VERTICAL TANGENCY PAVEMENT PUBLIC UTILITY & DRAINAGE EASEMENT RAVINE	R.O.W. RCP REM REV RR RT SAN SF SHLD. SL SMH ST STA. STD SW SY TBR T T-A T/C T/F T/P T/W T/WALL TEMP TRANS V.B. VCP V.V. WL WM	RIGHT-OF-WAY REINFORCED CONCRETE PIPE REMOVAL REVERSE RAILROAD RIGHT SANITARY SQUARE FOOT SHOULDER STREET LIGHT SANITARY MANHOLE STORM STATION STANDARD SIDEWALK SQUARE YARDS TO BE REMOVED TELEPHONE TYPE A TOP OF CURB TOP OF FOUNDATION TOP OF PIPE TOP OF WALK TOP OF WALL TEMPORARY TRANSFORMER VALVE BOX VITRIFIED CLAY PIPE VALVE VAULT WATER LEVEL WATER MAIN
---	--	---	--	--	---

MANHARD CONSULTING, LTD. IS NOT RESPONSIBLE FOR THE SAFETY OF ANY PARTY AT OR ON THE CONSTRUCTION SITE. SAFETY IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR AND ANY OTHER PERSON OR ENTITY PERFORMING WORK OR SERVICES. NEITHER THE OWNER NOR ENGINEER ASSUMES ANY RESPONSIBILITY FOR THE JOB SITE SAFETY OF PERSONS ENGAGED IN THE WORK OR THE MEANS OR METHODS OF CONSTRUCTION.



Environmental Consulting &  
Technology Inc  
403 W. St. Charles Road, Lombard,  
IL 60148  
(630)559-2000  
www.ectinc.com



UTILITY CONTACTS	
<b>ELECTRIC</b> COMED 4712 REILAND DRIVE JOLIET, IL 60433 (630) 576-7094 CONTACT: <b>GAS</b> NICOR GAS 1844 FERRY ROAD NAPERVILLE, IL 60563 (630) 388-3830 CONTACT: CONSTANCE LANE	<b>WATER</b> CITY OF DES PLAINES 1420 MINER STREET DES PLAINES, IL 60016 (847) 391-5390 CONTACT: TIM OAKLEY <b>TELEPHONE</b> AT&T 65 N. WEBSTER ST JOLIET, IL 60431 (770) 750-6181 CONTACT: JIM EVERETT <b>CABLE</b> COMCAST 688 INDUSTRIAL DRIVE ELMHURST, IL 60126 (630) 600-6346 CONTACT: MARTHA GIERAS

DATE	REVISIONS	BY	CHKD BY

**Manhard ECT CONSULTING LTD**  
Environmental Consulting &  
Technology Inc  
403 W. St. Charles Road, Lombard,  
IL 60148  
(630) 559-2000  
www.ectinc.com

OAKTON COMMUNITY COLLEGE COURTYARD REHABILITATION  
CITY OF DES PLAINES, ILLINOIS  
TITLE SHEET

PROJ MGR: JCM  
PROJ ASSOC: JCM  
DRAWN BY: JMO  
DATE: 11-04-22  
SCALE: N.T.S.

SHEET  
1 OF 7  
OCC.DPIL13

100% CD DRAWINGS (ADDENDUM #2) 01-19-23
























## RESIDENTIAL APPLICATION PAVER DETAIL


CREATED: MARCH 1, 2011  
REVISED: MARCH 6, 2014

FILE NAME: CS-1-PAVER.DWG

NOTES:  
This cross section is intended for preliminary design purposes only. Confirm site conditions and consult with a qualified design professional or installer prior to installation.

CROSS SECTION  
PAVERS ON GRANULAR BASE  
WITH EDGE RESTRAINT


DESIGNED TO CONNECT.



MATERIAL STANDARDS		
ITEM	BRAND	PRODUCT
MANHOLES/CATCHBASINS/INLETS IN OPEN AREAS AND PAVEMENT (SELF-SEALING LID WITH PROPER UTILITY MARKINGS)	NEENAH	CLOSED LID R-1772
		OPEN LID *1 SWALES AND DITCHES R-2502 A R-4340 B

\*1 WHEREVER STORMWATER COULD POSSIBLY ENTER STORM STRUCTURE (SEE MATERIAL STANDARDS DETAIL)

06-01-15  
MATERIAL STANDARDS  
S-10-MATERIALS



SHOULD A CONFLICT ARISE BETWEEN MANHARD DETAILS AND THE VILLAGE DETAILS, THE VILLAGE DETAILS SHALL TAKE PRECEDENCE.



MANHARD CONSULTING, LTD. STANDARD SPECIFICATIONS

GENERAL CONDITIONS

CONTRACTOR acknowledges and agrees that the use and reliance of these Plans and Specifications is sufficient consideration for CONTRACTOR'S covenants stated herein.

DEFINITION OF TERMS

- a. "CLIENT" shall mean Oakton Community College, which is the person or entity with whom Manhard Consulting, Ltd. has contracted with to prepare Civil Engineering PLANS and SPECIFICATIONS.
b. "ENGINEER" shall mean Manhard Consulting, Ltd., a Civil Engineering consultant on the subject project.
c. "PLANS and SPECIFICATIONS" shall mean the Civil Engineering PLANS and SPECIFICATIONS prepared by the ENGINEER, which may be a part of the contract documents for the subject project.
d. "CONTRACTOR" shall mean any person or entity performing any work described in the PLANS and SPECIFICATIONS.
e. "JURISDICTIONAL GOVERNMENTAL ENTITY" shall mean any municipal, county, state or federal unit of government from whom an approval, permit and/or review is required for any aspect of the subject project.

INTENT OF THE PLANS AND SPECIFICATIONS

The intent of the PLANS and SPECIFICATIONS is to set forth certain requirements of performance, type of equipment and structures, and standards of materials and construction. They may also identify labor and materials, equipment and transportation necessary for the proper execution of the work but are not intended to be infinitely determined so as to include minor items obviously required as part of the work. The PLANS and SPECIFICATIONS require new material and equipment unless otherwise indicated, and to require complete performance of the work in spite of omissions of specific references to any minor component part. It is not intended, however, that materials or work not covered by or properly inferred from any heading, branch, class or trade of the SPECIFICATIONS shall be supplied unless distinctly so noted. Materials or work described in writings, which so applied have a well-known technical or trade meaning, shall be held to refer to such recognized standards.

INTERPRETATION OF PLANS AND SPECIFICATIONS

- a. The CLIENT and/or CONTRACTOR shall promptly report any errors or ambiguities in the PLANS and SPECIFICATIONS to the ENGINEER. Questions as to meaning of PLANS and SPECIFICATIONS shall be interpreted by the ENGINEER, whose decision shall be final and binding on all parties concerned.
b. The ENGINEER will provide the CLIENT with such information as may be required to show revised or additional details of construction.
c. Should any discrepancies or conflicts on the PLANS or SPECIFICATIONS be discovered either prior to or after award of the contract, the ENGINEER'S attention shall be called to the same before the work is begun thereon and the proper corrections made. Neither the CLIENT nor the CONTRACTOR may take advantage of any error or omissions in the PLANS and SPECIFICATIONS. The ENGINEER will provide information when errors or omissions are discovered.

GOVERNING BODIES

All works herein proposed shall be completed in accordance with all requirements of any JURISDICTIONAL GOVERNMENTAL ENTITY, and all such pertinent laws, directives, ordinances and the like shall be considered to be a part of these SPECIFICATIONS. If a discrepancy is noted between the PLANS and SPECIFICATIONS and requirements of any JURISDICTIONAL GOVERNMENTAL ENTITY, the CLIENT and/or the CONTRACTOR shall immediately notify the ENGINEER in writing.

LOCATION OF UNDERGROUND FACILITIES AND UTILITIES

When the PLANS and SPECIFICATIONS indicate information pertaining to the location of existing underground facilities and utilities (including but not limited to water mains, sanitary sewers, storm sewers, electric, telephone, gas and cable TV lines), such information represents only the opinion of the ENGINEER as to the approximate location and elevation of such facilities and utilities. At the locations wherein detailed positions of these facilities and utilities become necessary to the new construction, including all points of connection, the CONTRACTOR shall furnish all labor and tools to verify or definitely establish the horizontal location, elevation, size and material (if appropriate) of the facilities and utilities. The CONTRACTOR shall notify the ENGINEER at least 48 hours prior to construction if any discrepancies in existing utility information or conflicts with existing utilities exist. The ENGINEER assumes no responsibility whatever with respect to the sufficiency or accuracy of the information shown on the PLANS and SPECIFICATIONS relative to the location of underground facilities and utilities, nor the manner in which they are removed or adjusted.

It shall be the CONTRACTOR'S responsibility prior to construction, to notify all Utility Companies of the intent to begin construction and to verify the actual location of all such facilities and utilities. The CONTRACTOR shall also obtain from the respective Utility Companies the working schedules for removing or adjusting these facilities.

UNSATURABLE SOILS

The PLANS have been prepared by the ENGINEER based on the assumption that all soils on the project are suitable to support the proposed improvements shown. The CLIENT or CONTRACTOR shall immediately notify the ENGINEER if he discovers or encounters an obstruction that prevents the installation of the improvement according to the line and grades shown on the PLANS.

PROTECTION OF TREES

All trees that are not to be removed shall be protected from damage. Trees shall not be removed unless requested to do so in writing by the CLIENT.

NOTIFICATION OF OWNERS OF FACILITIES AND UTILITIES

The CONTRACTOR shall notify all applicable Jurisdictional Governmental Entities or utility companies, i.e., water, sewer, electric, telephone, gas and cable TV prior to beginning any construction so that said entity or company can establish the location and elevation of underground pipes, conduits or cables adjoining or crossing proposed construction.

TRAFFIC CONTROL

The CONTRACTOR shall provide when required by any JURISDICTIONAL GOVERNMENTAL ENTITY, all signs, equipment, and personnel necessary to provide for safe and efficient traffic flow in all areas where the work will interrupt, interfere or cause a change in any form, the conditions of traffic flow that exist prior to the commencement of any portions of the work. The CLIENT may, at his discretion, require the CONTRACTOR to furnish traffic control under other and/or circumstances where in his opinion it is necessary for the protection of life and property. Emergency vehicle access shall be maintained at all times. Unless authorized by the CLIENT or CLIENT'S construction representative, all existing access points shall be maintained at all times by the CONTRACTOR. The need for traffic control shall be anticipated by the CLIENT.

WORK AREA

The CONTRACTOR, his agents and employees and their employees and all equipment, machinery and vehicles shall confine their work within the boundaries of the project or work area specified by the Client. The CONTRACTOR shall be solely liable for damage caused by him or his agents and employees and their equipment, machinery and vehicles on adjacent property or areas outside designated work areas.

UTILITY POLES

It shall be the responsibility of the CONTRACTOR to arrange for the relocation or bracing of existing utility poles that may be within the working limits of this contract. It is expressly understood that all work and costs connected with the maintenance of these utility poles, their temporary relocations, etc., shall be the responsibility of the CLIENT or the CONTRACTOR.

RESTORATION

It is the intent of these SPECIFICATIONS that clean-up and final restoration shall be performed immediately upon completion of each phase of the work, both inside and outside the Project, or when so directed by the CLIENT so that these areas will be restored as nearly as possible to their original condition or better, and shall include but not be limited to, restoration of maintained lawns and rights-of-way, roadways, driveways, sidewalks, ditches, bushes, hedges, trees, shrubs, fences, mailboxes, sewers, drain tiles, water mains, etc.

CLEANING UP

The CONTRACTOR shall at all times keep the premises free from accumulations of waste material or rubbish caused by his employees or work, and at the completion of the work he shall remove all his rubbish, tools, scaffolding and surplus materials and shall leave his work "boom clean" or its equivalent, unless more exactly specified.

ROAD CLEANING

The CONTRACTOR shall maintain roadways adjoining the project site free from mud and debris at all times. If mud and/or debris is carried into the roadways from vehicles entering onto the highway from either the CONTRACTOR'S trucks, his employees' vehicles, or his material suppliers, the CONTRACTOR shall immediately remove said mud and/or debris.

SAFETY AND PROTECTION

The CONTRACTOR shall be solely and completely responsible for the conditions of the job site, including safety of all persons and property during performance of the work. This requirement shall apply continuously and not be limited to normal working hours. The CONTRACTOR shall comply with all applicable Laws and Regulations relating to the safety of persons or property, or to the protection of persons or property from damage, injury, or loss; and shall erect and maintain all necessary safeguards for such safety and protection. CONTRACTOR'S duties and responsibilities for safety and for protection of the work shall continue until such time as all work is completed and the CLIENT has notified CONTRACTOR that the work is acceptable. The duties of the CONTRACTOR do not include review of the adequacy of either the CONTRACTOR'S or the general public's safety in, on, or near the construction site.

HOLD HARMLESS

To the fullest extent permitted by law, any CONTRACTOR, material supplier or other entity by use of these plans and specifications hereby waives any right of contribution and agrees to indemnify, defend, save and hold harmless the CLIENT and ENGINEER and its agents, employees and consultants from and against all manner of claims, causes, causes of action, damages, losses and expenses, including but not limited to, attorneys' fees arising out of, resulting from or in connection with the performance of any work, pursuant to or with respect to these plans and specifications. However, this indemnity shall not be construed to indemnify ENGINEER, its consultants, agents or employees against its own negligence.

Claims, damages, losses and expenses as these words are used in the Agreement shall mean and include, but not be limited to (1) injury or damage occurring by reason of the failure of or use of misuse of any hoist, riggings, blocking, scaffolding or any and all other kinds of items of equipment, whether or not the same be owned, furnished or loaned by any part or entity, including any contractor; (2) all attorneys' fees and costs incurred in bringing an action to enforce the provisions of this indemnity; (3) costs for time expended by the indemnified party and its employees, at its usual rates plus costs or travel, long distance telephone and reproduction of documents and (4) consequential damages.

In any and all claims against the CLIENT or ENGINEER or any of their agents or employees and consultants by any party, including any employee of the CONTRACTOR or any Subcontractor, anyone directly or indirectly employed by any of them or anyone for whose acts any of them may be liable, the indemnification obligation shall not be limited in any way by any limitation on the amount or type of damages, compensation or benefits payable by or for the CONTRACTOR or any Subcontractor under workers' or workmen's compensation acts, disability benefit acts or other employee benefit acts or any insurance maintained by CONTRACTOR or any Subcontractor or any other party.

INSURANCE

Any party using or relying on the plans, including any contractor, material supplier, or other entity shall obtain, (prior to commencing any work) general public liability insurance insuring against all damages and claims for any bodily injuries, death or property damage arising out of any work, including the construction work provided for in these plans, and shall name the CLIENT and ENGINEER and its consultants, agents and representatives as additional insureds under such insurance policy; provided that any party using or relying on these plans having obligations to maintain specific insurance by reason of any agreement with CLIENT or any CONTRACTOR or ENGINEER shall provide evidence and certificates of insurance as required by such contract or agreement. Such insurance must contain a clause stating that the insurance is primary coverage for ENGINEER and ENGINEER'S other applicable coverage is considered secondary. Such insurance shall not limit any liability of any party providing work or services or providing materials.

THIRD PARTY BENEFICIARY

Manhard Consulting, Ltd., the ENGINEER, is intended to be a third party beneficiary of this willing agreement and requirement.

Note: These Specifications are for Northern Illinois.

DETAILED SPECIFICATIONS

I. DEMOLITION

The CONTRACTOR shall coordinate with respective utility companies prior to the removal and/or relocation of utilities. The CONTRACTOR shall coordinate with the utility company concerning portions of work which may be performed by the Utility Company's forces and any fees which are to be paid to the utility company for their services. The CONTRACTOR is responsible for paying for all fees and charges.

Should removal and/or relocation activities damage features indicated to remain, the CONTRACTOR shall provide new materials/structures in accordance with the contract documents. Except for materials designed to be relocated on this plan, all other construction materials shall be new.

Prior to demolition occurring, all erosion control devices are to be installed. All existing utility lines and conduits located under proposed buildings shall be removed and properly backfilled. All utility lines and conduits located under, on-site roads, parking lots or sidewalks shall be filled with a flowable backfill and end plugged. All existing structures shall be removed. All existing utility lines located under landscape areas shall be left in place and plugged at all structures.

The CONTRACTOR is responsible for demolition, removal and disposal (in a location approved by all JURISDICTIONAL GOVERNMENT ENTITIES) of all structures, pads, walls, furnaces, foundations, road, parking lots, drives, drainage structures, utilities, etc., such that the improvements shown on these plans can be constructed. All demolition work shall be in accordance with all applicable federal, state and local requirements. All facilities to be removed shall be undercut to suitable material and brought to grade with suitable compacted fill material per the specifications.

The CONTRACTOR is responsible for obtaining all permits required for demolition and disposal. Electrical, telephone, cable, water, fiber optic cable and/or gas lines needing to be removed shall be coordinated by the CONTRACTOR with the affected utility company. CONTRACTOR must protect the public at all times with fencing, barriers, enclosures, and other appropriate best management practices. Continuous access shall be maintained for surrounding properties at all times during demolition.

All fire access lanes within the project area shall remain in service, clean of debris, and accessible for use by emergency vehicles. The CONTRACTOR shall coordinate water main work with the Fire Department and the JURISDICTIONAL GOVERNING ENTITY to plan the proposed improvements and to ensure adequate fire protection is available to the facility and site throughout this specific work and through all phases of construction. CONTRACTOR shall be responsible for any fire water main shut offs with the JURISDICTIONAL GOVERNING ENTITY during construction. Any costs associated with water main shut offs will be the responsibility of the CONTRACTOR and no extra compensation will be provided.

CONTRACTOR shall maintain all existing parking areas, sidewalks, drives, etc. clear and free from any construction activity and/or material to ensure easy and safe pedestrian and vehicular traffic to and from the site. CONTRACTOR shall coordinate phase all construction activity within proximity of the building and utility interruptions with the facility manager to minimize disturbance and inconvenience to facility operations.

CONTRACTOR may limit saw-cut and pavement removal to only those areas where it is required as shown on these construction plans, however if any damage is incurred on any of the surrounding pavement, etc. the CONTRACTOR shall be responsible for ITS removal and repair.

Any existing wells encountered shall be exposed and sealed 3' below proposed finish grade by the CONTRACTOR in accordance with Section 920.120 (latest edition) of the Illinois Water Well Construction Code, Department of Public Health, and all applicable local rules and regulations. CONTRACTOR is responsible for obtaining all permits required by JURISDICTIONAL GOVERNMENTAL ENTITIES for abandoning existing wells.

Any existing septic tanks and grease traps encountered shall have all liquids and solids removed and disposed of by a licensed commercial hauler in accordance with JURISDICTIONAL GOVERNING ENTITY regulations, and the tank and grease traps shall then be filled with suitable materials or removed from the site and disposed of by the CONTRACTOR. Voids left by any item removed under any proposed building, pavement, walk, etc. or within 24" thereof shall be filled and compacted with suitable materials by the CONTRACTOR.

The CONTRACTOR shall be responsible for the disconnection of utility services to the existing buildings prior to demolition of the buildings. Any material containing asbestos found within existing structures shall be removed from the site and disposed of off-site by the CONTRACTOR in accordance with County, State and Federal regulations.

CONTRACTOR shall develop and implement a daily program of dust control and shall submit and obtain JURISDICTIONAL GOVERNING ENTITY approval of dust control procedures prior to demolition of any structures. Modification of dust control procedures shall be performed by the CONTRACTOR to the satisfaction of the JURISDICTIONAL GOVERNING ENTITY as requested.

The CONTRACTOR shall coordinate all demolition with the JURISDICTIONAL GOVERNING ENTITY and CLIENT to ensure protection and maintenance of sanitary sewer and water utilities as necessary and to provide stormwater conveyance until new facilities are constructed, tested and placed into operation.

The locations of all existing utilities shown on this plan have been determined from the best information available and are given for the convenience of the CONTRACTOR and are not to be interpreted as the exact location, or as the only obstacles that may occur on the site. The ENGINEER assumes no responsibility for their accuracy. Prior to the start of any demolition activity, the CONTRACTOR shall notify the utility companies for location of existing utilities and shall verify existing conditions and proceed with caution around any anticipated features.

The CONTRACTOR is responsible for removing the existing irrigation system in the areas of proposed improvements. The contractor shall cap the existing irrigation system to remain such that the remaining system shall continue to function properly.

The parking lot shall be completed in sections such that it does not interrupt the facility operations. The CONTRACTOR shall coordinate with the construction manager for work to be performed.

II. EARTHWORK

STANDARDS

This work shall be completed in conformance with the applicable sections of the Standard Specifications for Road and Bridge Construction, Department of Transportation, State of Illinois, latest edition except as modified below.

SOIL BORING DATA

Copies of results of soil boring and reports, if such borings were taken by the CLIENT in the vicinity of the proposed construction site, should be made available by the CLIENT to the CONTRACTOR. These borings are presented for whatever purpose the CONTRACTOR chooses to make of them. The ENGINEER makes no representation or warranty regarding the number, location, spacing or depth of borings taken, nor of the accuracy or reliability of the information given in the results thereof.

Further, the ENGINEER does not assume responsibility for the possibility that during construction, the soil and groundwater condition may be different than indicated. Neither does the ENGINEER assume responsibility for variations of soil and groundwater at location between borings. The CONTRACTOR is required to make its own borings, explorations and observations to determine soil and groundwater conditions.

EARTHWORK CALCULATIONS AND CROSS SECTIONS

The CONTRACTOR understands that any earthwork calculations, quantities or cross sections that have been furnished by the ENGINEER are for information only and are provided without any guarantee by the CLIENT or ENGINEER whatsoever as to their sufficiency or accuracy. CONTRACTOR warrants that he has performed his own subsurface investigations as necessary and his own calculations and cross sections to determine site soil conditions and earthwork volumes. The ENGINEER makes no representation or guarantee regarding earthwork quantities or that the earthwork for this project will balance due to the varying field conditions, changing soil types, allowable construction tolerances and construction methods that are beyond the control of the ENGINEER.

CLEARING, GRUBBING AND TREE REMOVAL

The site shall be cleared, grubbed, and trees and stumps removed where designated on the PLANS. Trees designated to remain shall be protected from damage.

TOPSOIL STRIPPING

Upon completion of demolition, clearing, grubbing and tree removal, all topsoil shall be stripped from under all buildings and pavements areas, and other areas necessary to complete the work. Topsoil stripped shall be placed in stockpiles in locations as designated by the CLIENT. Existing topsoil should not be stripped from future planting areas.

TOPSOIL RESPAREAD

Upon completion of roadway and/or parking lot improvements and installation of underground utilities a minimum of six inches (6") of topsoil shall be respread over all unpaved areas which have been disturbed by earthwork construction, except building pads and other designated areas, which shall be kept free from topsoil.

SEEDING

Upon completion of topsoil respread, the CONTRACTOR shall apply seed and fertilizer to all respread areas in accordance with IDOT standards or as designated on landscape drawings and specifications provided by the CLIENT.

SODDING

Upon completion of topsoil respread, the CONTRACTOR shall install sod to all areas designated on the plans or as designated on the landscape drawings and specifications provided by the CLIENT.

EXCAVATION AND EMBANKMENT

Upon completion of topsoil stripping, all excavation and embankments shall be completed as shown on the PLANS. All suitable excavated materials shall be hauled, placed (moisture conditioned if necessary and compacted) in the embankment areas. The CONTRACTOR shall include all dewatering, temporary ditching and culverts necessary to complete the excavation and embankment.

Specifically included in the scope of Excavation and Embankments is grading and shaping of all cut or fill areas including swales and ditches; handling of sewer silt, etc., and all work required to provide positive drainage at the end of each working day and upon completion of a section.

The CONTRACTOR shall be responsible for the excavation of all swales and ditches and for the excavation or filling of the roads, building pads and parking lots within the work limits to lines & grades shown on the plans. He shall be responsible for obtaining compaction in accordance with the minimum values listed in the table below for all embankments unless more stringent values are listed in the soils report or are approved by the CLIENT, and to use any method approved by the CLIENT necessary to obtain this compaction (i.e., soil fabric or any undercutting that may be required).

Table with 5 columns: Percent Compaction, Type Material, Standard, Pavement & Floor Slabs, Grass Areas. Rows include Sandy Soils, Modified Proctor, 95%, 90%; Clayey Soils, Standard Proctor, 95%, 90%.

The CONTRACTOR shall notify the CLIENT if proper compaction cannot be obtained so that the CLIENT may determine what remedial measures may be needed.

A soils testing firm employed by the CLIENT shall determine which soils are unsuitable. Materials in their natural state being defined as unsuitable that would be suitable material if moisture conditioned, shall be conditioned by the CONTRACTOR and used as suitable embankment material or hauled from the site.

For purposes of definition, unsuitable material shall be as follows unless determined otherwise by the Soils Engineer:

- 1. Any soil whose optimum moisture content exceeds 25%.
2. Any cohesive soil with an unconfined compressive strength of 1.5 tons per square foot or less.
3. Any soil whose silt content exceeds 60% by weight.
4. Any soil whose maximum density is less than 100 pounds per cubic foot.
5. Any soil containing organic, deleterious, or hazardous material.

Upon completion of excavation and shaping of the water retention areas intended to maintain a permanent pool of water, all silt seams and granular or sandy soils shall be removed to a minimum depth of three feet below the subgrade and replaced with an impermeable clay liner, including adjacent to and under storm sewer inlets and outlets. It is the intent of these PLANS and SPECIFICATIONS that the CONTRACTOR shall prepare the lake bottoms, side slopes, and connection thereof such that the lakes will maintain the proposed normal water level and that leakage does not exceed 1/2" inch per week.

Ditches and swales are to be excavated to the lines and grades indicated on the PLANS. All suitable materials excavated from the ditches shall be used in construction of the embankments.

The CONTRACTOR shall notify the CLIENT immediately upon encountering groundwater during excavation. If in the opinion of the CLIENT or the JURISDICTIONAL GOVERNING ENTITY this condition necessitates the installation of perforated drain tile bedded in washed gravel or open storm sewer joints wrapped with fabric, the CONTRACTOR shall install the same.

During excavation and embankment, grades may be adjusted to achieve an overall site earthwork balance. The CONTRACTOR shall cooperate fully with the CLIENT in adjustment of grades, construction methods and placement of material to meet the above goals and shall immediately advise CLIENT if he believes that the earthwork will not balance.

It is the intent of these PLANS that storm waters falling on the site be diverted into sedimentation / lake / detention basins during construction. The CONTRACTOR shall construct and maintain any temporary ditches or swales that are necessary to accomplish this prior to beginning mass excavation.

EROSION CONTROL

Suitable erosion control practices shall be maintained by the CONTRACTOR in accordance with Illinois Urban Manual and all applicable Soil Erosion and Sedimentation Control ordinances and the PLANS.

UNDERCUTTING DURING EARTHWORK

If the subgrade cannot be dried adequately by discing as outlined above for placement of material to planned grades and if the CLIENT determines that the subgrade does not meet the standards set forth above, the CLIENT may require undercutting.

MISCELLANEOUS CONTRACT ITEMS

The following items may be required at the CLIENT'S option, as indicated on the PLANS or as required by the JURISDICTIONAL GOVERNING ENTITY:

- (1) GEOTEXTILE FABRIC: Geotextile fabric or approved equal shall be provided in areas as designated by the CLIENT, as indicated on the PLANS or as required by the JURISDICTIONAL GOVERNING ENTITY where proper compaction of embankments over existing soft soils is not possible. Geotextile fabric shall meet the material specifications of and shall be installed in accordance with the above standards.
(2) EROSION CONTROL BLANKET: Erosion control blanket or approved equal shall be provided in areas as designated by the CLIENT, as indicated on the PLANS or as required by the JURISDICTIONAL GOVERNING ENTITY for the stabilization of disturbed areas. Erosion control blanket shall meet the material specifications of and shall be installed in accordance with the above standards, the Illinois Urban Manual and/or the details shown on the PLANS.

III. UNDERGROUND IMPROVEMENTS

A. GENERAL

STANDARDS

All underground improvements shall be constructed and tested in accordance with the Standard Specifications for Water and Sewer Construction in Illinois and Standard Specifications for Road and Bridge Construction, Department of Transportation, State of Illinois, latest edition. In the event of conflicting guidelines, the more restrictive shall govern.

SELECTED GRANULAR BACKFILL

Selected Granular Backfill shall be required for all sewer and water main trenches lying under existing or proposed streets, driveways, parking lots and within 24" thereof, and where noted on PLANS. All material placed in such trenches shall be in accordance with the above standards.

MANHOLES, CATCH BASIN, INLETS & VALVE VAULTS

All Manholes, Catch Basins, Inlets, and Valve Vaults shall be constructed of reinforced precast concrete ring construction with tongue and groove joints in conformance with the latest revision of ANSI designation C-478. All joints between sections and frames (except sanitary manholes, see Section IIB Manholes below) shall be sealed with mastic type bituminous jointing compound. CONTRACTOR shall remove all excess mastic on inside of structure and butter joints with mortar. Manholes are to be offset concrete except that no cone shall be used on storm manholes 6'-0" deep or less in which case a reinforced concrete flat top section shall be used, and Valve Vaults shall have concentric cones. Only concrete adjustment rings will be permitted where necessary and shall be limited to two adjustment rings totaling not more than 8" in height. All manholes and catch basin steps shall be copolymer polypropylene with continuous 1/2" steel reinforcement as manufactured by MA Industries, or approved equal.

\*AUGER/BORING AND CASING - INTENTIONALLY OMITTED

\*AUGER (OPEN BORE) - INTENTIONALLY OMITTED

\*HORIZONTAL AND VERTICAL SEPARATION OF WATER AND SEWER MAINS - INTENTIONALLY OMITTED

STRUCTURE ADJUSTMENTS

Structures shall be adjusted to the finished grade as shown on PLANS.

\*B. SANITARY SEWERS AND APPURTENANCES - INTENTIONALLY OMITTED

\*C. WATER MAINS AND APPURTENANCES - INTENTIONALLY OMITTED

D. STORM SEWERS AND APPURTENANCES

STORM SEWER PIPE

- Storm sewer pipe shall conform to the following:
(1) Reinforced concrete pipe minimum Class IV in conformance with the latest revision of ASTM designation C76 with C443 flexible gasket joint, except that bituminous mastic joints may be used in grass areas.
(2) Polyvinyl Chloride (PVC) Pipe: ASTM D3034 (4-inch thru 15-inch) or ASTM F679 (18-inch thru 36-inch), rated SDR 35, continually marked with manufacturer's name, pipe size, cell classification, SDR rating. Joints shall be flexible elastomeric seals conforming to ASTM D3212.
(3) Ductile Iron Pipe (DIP) shall conform to ANSI/AWWA C1512.1.5, Class 50 cement lined with push on type joints conforming to ANSI/AWWA C1119.21.11.
(4) Spiral Rib Metal Pipe Type 1R- 18-inch diameter and greater. Pipe ends shall be re-corrugated and installed with semi-corrugated Huggar type brands and "O" ring gaskets. (Only permitted with Municipality approval and/or when specifically indicated on PLANS.)
(5) High Density Polyethylene Pipe (HDPE) Smooth Interior, AASHTO Designation M252 and M294, maximum diameter of 48 inches. Pipe joints and fittings shall be welded gasketed joints. No band seals will be allowed. (Only permitted in landscape areas with Municipality Approval and/or when specifically indicated on PLANS.)
(6) Polypropylene (PP) Pipe shall have a smooth interior and annular exterior corrugations and shall meet or exceed ASTM F2081 and AASHTO M300. Pipe shall be joined with a gasketed integral bell & spigot joint meeting the requirements of ASTM F2081. PP Pipe shall be watertight according to the requirements of ASTM D3212. Spigots shall have gaskets meeting the requirements of ASTM F477. (Only permitted with Municipality Approval and/or when specifically indicated on PLANS.)
(7) Polyvinyl Chloride (PVC) large diameter closed profile gravity sewer pipe, UNI-B-8: ASTM F794. (Only permitted with Municipality Approval and/or when specifically indicated on PLANS.)
(8) Corrugated Steel (Metal) Pipe (CSR or CMP), ASTM A760, 16 gauge unless noted on PLANS. Corrugated steel pipe may be round pipe, arch pipe, or slotted drainage as indicated on PLANS. Slotted drainage pipe shall have 1.75 inches wide drain watery openings and 6 inches minimum height drain guide. (Only permitted with Municipality approval and/or when specifically indicated on PLANS.)

Precast tees, bends, and manholes may be used if permitted by the JURISDICTIONAL GOVERNMENTAL ENTITY.

Storm sewer shall include bedding and trench backfill.

MANHOLES, INLETS & CATCH BASINS

Manholes, Inlets and Catch Basins shall be constructed in conformance with Section IIA Manholes, etc. above. The space between connecting pipes and the wall of the manhole shall be completely filled with non-shrink hydraulic cement mortar. Frames and lids shall be Neenah or approved equal unless specified otherwise on the PLANS. All frames and grates shall be provided such that the flange fully covers the opening plus 2" of the structure as a minimum. Provide "Vane" Type Frame & Grate for all structures located in curb where gradient exceed 2.0%. Manholes shall include steps, frame & grate, bedding and trench backfill.

\*FLARED END SECTION - INTENTIONALLY OMITTED

\*RIP RAP - INTENTIONALLY OMITTED

FOUNDATION, BEDDING AND HAUNCHING

Foundation, Bedding and Haunching shall be wet coarse aggregate or moist fine aggregate in accordance with the above standards and placed as shown on the detail.

UNDERDRAINS

Pipe underdrains shall be corrugated flexible plastic pipe conforming to AASHTO Designation M252 perforated corrugated polyethylene pipe (PE) with a smooth interior of the diameter indicated on the PLANS and wrapped in a soil filter fabric supplied and installed by the CONTRACTOR. Performances may be circular or octagonal, but shall provide a minimum inlet area of 1.0 square inch per 2.0 linear feet of pipe. CONTRACTOR shall submit fabric and pipe catalogue specifications for approval by the CLIENT. CONTRACTOR shall bed and backfill the underdrain in one of the following IDOT gradations of aggregate (CA-5, CA-7, CA-11, CA-14 or CA-15).

MISCELLANEOUS

- (1) All existing field drainage tile or storm sewers encountered or damaged during construction shall either be restored to their original condition, properly repaired and/or connected to the storm sewer system.
(2) Footing drains shall be connected to pump pumps or discharged directly into storm sewers. Footing drains or drainage tile shall not be connected to the sanitary sewer.

CONNECTION FOR STORM SERVICE TO STORM MAIN

Connections of storm sewer services to storm sewer mains should be made with manufactured tees when available. Availability of manufactured tees will be a function of the storm sewer material and pipe diameter size of the service sewer and main. If manufactured tees are not reasonably available, connections should be made in accordance with manufacturer's recommendations for all storm sewer other than concrete pipe. For concrete pipe connections without manufactured tees the storm sewer main shall be cut and bored and the service sewer connected using non-shrink grout for the void between pipes. The service sewer shall be cut flush with the inside wall of the sewer main and not extend into the inside flow area of the main or otherwise impede flow.

IV. ROADWAY AND PARKING LOT IMPROVEMENTS

STANDARDS

Work shall be completed in accordance with the applicable sections of the Standard Specifications for Road and Bridge Construction, Department of Transportation, State of Illinois, latest edition (hereinafter referred to collectively as the "Standard Specifications") except as modified below and except that payment will be defined as detailed in the contract documents between the CLIENT and the CONTRACTOR. Supplementing the Standard Specifications shall be the applicable sections of the latest editions of the "Supplemental Specifications and Recurring Special Provisions" the "Manual on Uniform Traffic Control Devices for Streets and Highways" and the Illinois Supplement thereto, (hereinafter referred to collectively as the "MUTCD"). Any references to "ENGINEER" in the "Standard Specifications" shall be interpreted as the CLIENT or CLIENT'S Construction Representative.

SUBGRADE PREPARATION

The CONTRACTOR shall be responsible for all subgrade compaction and preparation to the lines and grades shown on the plans.

AGGREGATE BASE COURSE TYPE 'B'

Aggregate Base Course Type B shall be limited to CA-6 or CA-10 gradation. Aggregate base courses shall be proof rolled as outlined below.


PROOF ROLL

The CONTRACTOR shall proof roll the subgrade with either a 2-axle truck loaded to 27,000 lbs. Or a 3-axle truck loaded to 45,000 lbs. or as specified by the JURISDICTIONAL GOVERNING ENTITY. The CLIENT and JURISDICTIONAL GOVERNING ENTITY shall observe and approve the proof rolling of the subgrade and the base course. Proof rolling tolerances shall be a maximum deflection of 1" for the subgrade and 1/2" for












- GENERAL PLANTING NOTES**
- CONTRACTOR SHALL PROVIDE FRESH TOPSOIL OR AMEND EXISTING TOPSOIL AS INDICATED ON SHEET L1.0.
  - PRIOR TO CONSTRUCTION THE INSTALLER SHALL BE RESPONSIBLE FOR LOCATING ALL UNDERGROUND UTILITIES AND SHALL AVOID DAMAGE TO ALL UTILITIES DURING CONSTRUCTION.
  - CONTRACTOR TO PROVIDE ALL PLANT MATERIAL AND ACCESSORIES.
  - CONTRACTOR IS RESPONSIBLE FOR MAINTENANCE/REPLACEMENT OF INSTALLED PLANTS PER THE SPECIFICATIONS. SECTION 329300 INCLUDES A WARRANTY/MAINTENANCE PERIOD OF:
    - ONE YEAR FROM THE DATE OF SUBSTANTIAL COMPLETION FOR TURFGRASS;
    - ONE YEAR FROM THE DATE OF SUBSTANTIAL COMPLETION FOR WOODY TREES AND SHRUBS;
    - AND TWO YEARS FROM THE DATE OF SUBSTANTIAL COMPLETION FOR HERBACEOUS PERENNIALS AND GRASSES.
  - MAINTENANCE DURING THE WARRANTY/MAINTENANCE PERIOD INCLUDES, BUT IS NOT LIMITED TO: WATERING, HERBICIDE APPLICATIONS, MULCHING, PRUNING, MOWING, AND FERTILIZING.
  - NOTE THAT PLANT LIST QUANTITIES ARE FOR THE INSTALLER'S CONVENIENCE ONLY. INSTALLER SHALL VERIFY ALL QUANTITIES.
  - ALL PLANTED MATERIAL SIZES AND MEASUREMENTS, INCLUDING TRUNK, HEAD AND SPREAD SIZES, CONTAINER AND ROOT BALL SIZES, QUALITY AND CONDITION SHALL CONFORM TO THE STANDARD SET FORTH IN THE CURRENT ISSUE OF "AMERICAN STANDARD FOR NURSERY STOCK."
  - ALL PLANTS MUST BE HEALTHY, VIGOROUS MATERIAL, FREE OF PESTS AND DISEASE.
  - ALL PLANTS MUST BE CONTAINER-GROWN OR BALLED AND BURLAPPED AS INDICATED IN THE PLANT LIST.
  - ALL TREES MUST BE STRAIGHT TRUNKED AND FULL-HEADED AND MEET ALL REQUIREMENTS SPECIFIED.
  - ALL PLANTS ARE SUBJECT TO THE APPROVAL OF THE LANDSCAPE ARCHITECT AND OWNER BEFORE, DURING AND AFTER INSTALLATION.
  - ALL TREES MUST BE GUYED OR STAKED AS SHOWN IN THE DETAILS OR WRITTEN SPECIFICATIONS.
  - ALL PLANTING AREAS MUST BE COMPLETELY MULCHED AS SPECIFIED.
  - PRIOR TO MULCHING APPLY A PRE-EMERGENT HERBICIDE (APPROVED BY LANDSCAPE ARCHITECT AND OWNER) AS RECOMMENDED BY THE MANUFACTURER TO PREVENT RECURRING WEED AND GRASS GROWTH.
  - ALL TREES IN LEAF AFTER BEING DUG AT THE NURSERY SOURCE SHALL BE ACCLIMATED FOR TWO (2) WEEKS MINIMUM UNDER A MIST SYSTEM PRIOR TO INSTALLATION.
  - ALL LARGE PIECES OF STONE AND CONCRETE RESIDUE OVER 1" IN DIAMETER ARE TO BE REMOVED FROM PLANTING BEDS TO A 18" DEPTH AND REPLACED WITH CLEAN TOPSOIL.



- NOTES**
- REFER TO CIVIL SHEETS FOR PAVING AND CURB LAYOUT, GRADING, DRAINAGE, AND RELATED DETAILS
  - REFER TO CIVIL SHEETS FOR BASES FOR RELOCATED SCULPTURE
  - REFER TO ELECTRICAL SHEETS FOR NEW LIGHTPOLES AND ELECTRICAL SERVICE.
  - REFER TO SPECIFICATION 329300 "EXTERIOR PLANTINGS" FOR PLANTS, SOIL, AND MULCH INSTALLATION AND MAINTENANCE.
  - REFER TO SPECIFICATION 129300 "SITE FURNISHINGS" FOR BENCHES.
  - CONTRACTOR SHALL STAKE ALL TREE/SRUB LOCATIONS AND LAYOUT ALL HERBACEOUS PLANTING AREAS FOR REVIEW AND ACCEPTANCE BY LANDSCAPE ARCHITECT PRIOR TO PLANTING PER 329300, PART 3.4.
  - REFER TO CIVIL SHEETS FOR INSTALLATION OF UNIT PAVERS. CONTRACTOR SHALL FOLLOW PATTERNS SHOWN ON THIS SHEET.
    - PLANS REQUIRE THE FOLLOWING QUANTITY OF PAVERS APPROXIMATELY:
      - 2,772 SF OF HALF-SIZED BRUSSELS PAVERS
      - 1,981 SF OF STANDARD-SIZED BRUSSELS PAVERS
      - 1,569 SF OF XL-SIZED BRUSSELS PAVERS
    - OWNER WILL SUPPLY CONTRACTOR WITH APPROXIMATELY 2,024 SQUARE FEET OF HALF-SIZE BRUSSELS PAVERS AND 2,942 SQUARE FEET OF STANDARD SIZE BRUSSELS PAVERS. CONTRACTOR MAY SAWOUT STANDARD SIZE UNITS IN HALF TO MAKE ADDITIONAL HALF-SIZED UNITS.
      - CONTRACTOR SHALL CONFIRM ALL REQUIRED QUANTITIES AND PROVIDE ADDITIONAL PAVERS AS NEEDED TO COMPLETE THE WORK.



DATE	REVISIONS

**ECT**  
Environmental Consulting & Technology, Inc.  
40 West Chicago Street, Suite 400  
Chicago, Illinois 60610  
(833)359-2000  
www.ectinc.com

**Manhard CONSULTING LTD**  
Landscape Architects + Planners  
Civil Engineers + Surveyors + Water Resources Engineers + Water & Wastewater Engineers  
Construction Managers + Environmental Scientists + Landscape Architects + Planners

**OAKTON COMMUNITY COLLEGE COURTYARD REHABILITATION**  
**CITY OF DES PLAINES, ILLINOIS**  
**PLANTING PLAN**



PROJ MGR: JAC  
PROJ ASSOC: JAC  
DRAWN BY: BEP/IB  
DATE: 10-27-22  
SCALE: 1"=10'

**SHEET**  
**L2.0**  
OCC.DPIL13











NOTE:  
 1. MAINTAIN PLANT PROTECTION FENCE AROUND ALL EXISTING TREES, OR AS SHOWN IN PLANS, FOR THE ENTIRE DURATION OF THE PROJECT.  
 2. REFER TO SPECIFICATION 015639 'TEMPORARY TREE AND PLANT PROTECTION'.

**G** BENCH PIERS  
 © 2022 by Environmental Consulting & Technology, Inc.  
 1 1/2"=1'-0"  
 L3.0 Construction Details


**E** PLANT PROTECTION ZONE  
 © 2022 by Environmental Consulting & Technology, Inc.  
 1/4"=1'-0"  
 L3.0 Construction Details



NOTES:  
 1. TREES SHALL BE BALLED AND BURLAPPED (B&B) WITH NO EXCEPTIONS.  
 2. TREES SHALL BE MULCHED AS PER SPECIFICATIONS.


**C** GROUNDCOVER AND PERENNIAL PLANTING  
 © 2022 Environmental Consulting & Technology, Inc.  
 1"=1'-0"  
 L3.0 Construction Details

**A** DECIDUOUS TREE PLANTING  
 © 2022 Environmental Consulting & Technology, Inc.  
 3/8"=1'-0"  
 32 90 00\_Deciduous Tree Planting-0.0313




APPROVAL		FORMS+SURFACES	
NAME	DATE	NAME	DATE
_____	_____	_____	_____
_____	_____	_____	_____

**F** BENCH  
 © 2022 Environmental Consulting & Technology, Inc.  
 NTS



NOTES:  
 1. FIT COBBLE TOGETHER TIGHTLY AND TAMP INTO 1"-2" LAYER OF STONE SCREENINGS.  
 2. DRESS JOINTS WITH ADDITIONAL STONE SCREENINGS AND REPEAT WATERING IN PROCEDURES UNTIL SCREENINGS COMPLETELY FILL JOINTS. ALLOW WATER TO DRAIN COMPLETELY BEFORE ADDING ADDITIONAL SCREENINGS.

**D** COBBLE PAVING  
 © 2022 Environmental Consulting & Technology, Inc.  
 3" = 1'-0"  
 L3.0 Construction Details.dwg



**B** SHRUB PLANTING  
 © 2022 Environmental Consulting & Technology, Inc.  
 1 1/2" = 1'-0"  
 32 93 00\_Shrub Planting\_02.0.1250

DATE	REVISIONS

**ECT**  
 Environmental Consulting & Technology, Inc.  
 40 W. Jackson Street, Suite 100  
 Lombard, IL 60148  
 (630) 359-2000  
 www.ectinc.com

**Manhard CONSULTING LTD.**  
 Manhard Consulting Ltd.  
 1100 West 17th Street, Suite 100  
 Oshkosh, WI 54901  
 (920) 231-1100  
 www.manhardconsulting.com

OAKTON COMMUNITY COLLEGE COURTYARD REHABILITATION  
 CITY OF DES PLAINES, ILLINOIS  
 LANDSCAPE DETAILS

PROJ. MGR.: JAC  
 PROJ. ASSOC.: JAC  
 DRAWN BY: BEP/IB  
 DATE: 10-27-22  
 SCALE: 1"=10'

SHEET  
**L3.0**  
 OCC.DPIL13







3. To include the following: ADDENDUM #2 CHANGE LOG FOR OAKTON COLLEGE COURTYARD REHABILITATION CITY OF DES PLAINES, ILLINOIS



Civil Engineering  
Surveying  
Water Resources Management  
Water & Wastewater Engineering  
Construction Management  
Environmental Sciences  
Landscape Architecture  
Land Planning

**ADDENDUM #2 CHANGE LOG  
FOR  
OAKTON COLLEGE COURTYARD REHABILITATION  
CITY OF DES PLANES, ILLINOIS**

Prepared by:

EVAN BOULWARE  
MANHARD CONSULTING, LTD.  
116 W. ILLINOIS ST., FLOOR 7  
CHICAGO, ILLINOIS 60654  
PHONE: (847) 325-7093

OCC.DPIL.13  
January 13, 2023





**ADDENDUM #2 CHANGE LOG  
 FOR  
 OAKTON COLLEGE COURTYARD REHABILITATION**

**Summary** - The purpose of this report is to present all pay item changes included in the updated plan set in the issued Addendum #2. For exact locations of the noted updates please see the latest issue of the final plan set Oakton Community College Courtyard Rehabilitation.

**PLAN SET REVISIONS:**

**Sheet 1 – Title Sheet**

- Grading and utility sheets separated for clarity

**Sheet 2 – Existing Conditions and Demolition Plan**

- Existing electrical junction box in southwest quadrant of lowered central courtyard to be adjusted to grade
- Existing concrete walk in lowered courtyard called out as to be removed

**Sheet 4 – Grading Plan**

- Additional inlet protection added to proposed inlet southwest of central courtyard area.
- New weep holes to be drilled into concrete wall at locations where existing weepholes are blocked by new paver layout in lower courtyard area
- Alternate option calling for trench drains in lower courtyard to be removed and replaced if adjusting to grade is found to be infeasible
- Sanitary manhole in raised planter to be sawcut to proposed rim grade

**Sheet 5 – Utility Plan**

- Utility notes added for clarity
- Inlet proposed southwest of central courtyard area
- 44’-8” Storm line proposed to tee into existing storm under central courtyard area

**Sheet 6 – Construction Details**

- Sidewalk detail added
- Inlet detail added
- Material standards detail added
- Pipe installation detail added

**BID ITEM REVISIONS:**

90	ADJUST ELECTRICAL JUNCTION BOX TO GRADE		EA
91	DRILL WEEP HOLES INTO CONCRETE WALL		LS
92	6" TRENCH DRAIN FRAME AND GRATE		EA
93	2'-0" DIAMETER INLET		EA
94	8" PVC STORM SEWER PIPE AND TRENCH BACKFILL		LF

*All other specifications, terms, and conditions noted in the original bid documents remain in effect and unchanged.*

**Please sign and return this addendum with your bid.**